can-am.

DEFENDER X MR HD10

				ITC
_		пι		HTS
	\sim		. ~ .	

Rear

IIIdiiLidiiio				
TOUGH	Heavy-duty Rotax® engine Smooth, durable and responsive transmission True Can-Am DNA with a strong identity			
CAPABLE	Work or ride with confidence Meaningful and versatile functionality Easy handling and capabilities	Cat-an		
CLEVER	Advanced comfort and intuitive cockpit with optimized visibility Multifunction cargo box with sturdy tailgate and smart storage 1 year maintenance-free and easy access to key maintenance components			
PLATFORM FEATURES	83 in. (211.5 cm) wheelbase 15 in. (38.1 cm) of ground clearance Dynamic Power Steering (DPS) ECO™ / ECO™ Off / Work modes	Liquid Titanium & Magma Red / HD10 DIMENSIONS & CAPACITIES		
	2,500 lb (1,134 kg) towing capacityMultifunction cargo box	Chassis/Cage	Profiled cage, ROPS approved	
	Rear differential with Turf mode	Estimated Dry Weight	1,697.6 lb (770 kg)	
SPECIFIC TO X mr PACKAGE	• 64 in. (162.6 cm) wide with Arched A-arm	LxWxH	129.4 x 64 x 82 in. (328.6 x 162.6 x 208.3 cm)	
	LED SignatureSmart-Lok front differential	Wheelbase	83 in. (211.5 cm)	
	Strategically positioned engine air intake and CVT inlet /	Ground Clearance	15 in. (38.1 cm)	
	outlet	Cargo Box Dimensions	38 x 54.5 x 12 in. (96.5 x 138.4 x 30.5 cm)	
	 14 in. cast-aluminum wheels 30 in. ITP Cryptid tyres VERSA-PRO bolster bench seat, reinforced seat skin 	Cargo Box Capacity	1,000 lb (454 kg)/California only: 600 lb (272.2 kg)	
	featuring X package trims and adjustable driver seat	Power Tilt Bed	N/A	
	HMWPE full skid plate4,500 lb (2,014 kg) winch	Tailgate Load Capacity	250 lb (113.4 kg)	
	Heavy-duty front steel bumper Aluminum rock slider 7.6 in. digital display with keypad Brake holding mechanism	Storage Capacity	Total: 16.2 gal (61.3 L) Under dash: 6 gal (22.8 L) Waterproof and removable box under passenger seat: 5.6 gal (21 L) Dash: 2 gal (7.7 L) Water-resistant and removable toolbox: 1.7 gal (6.3 L) Armrests and cup holders: 0.9 gal (3.5 L)	
ENGINE HD10		Towing Capacity	2,500 lb (1,134 kg)	
Туре	82 hp/69 lb-ft, Rotax® 976 cc, V-twin, liquid-cooled with strategically positioned engine air intake	Payload Capacity	1,750 lb (793.8 kg)	
Fuel Delivery System	Intelligent Throttle Control (iTC™) with Electronic Fuel Injection (EFI)	Fuel Capacity	10.6 gal (40 L)	
r der Denvery Gystern		Person Capacity	3	
Transmission	PRO-TORQ CVT Transmission with Quick Response System (QRS), Electronic Drive Belt Protection, lower gearing ratio	FEATURES		
	and high-airflow ventilation with strategically positioned CVT air intake and exhaust Extra L/H/N/R/P	Gauge	7.6 in. wide digital display with keypad: speedometer, tachometer, odometer, trips and hour meters, fuel, gear position, ECO™/ECO™	
Drive Train	Selectable Turf Mode/2WD/4WD TRAIL/4WD MUD with exclusive Smart-Lok* technology		Off/Work modes, seat belt and 4 x 4 indicator, front and rear diff. lock indicators, diagnostics, clock, battery voltage, engine temperature	
Driving Assistance	Electronic Hill Descent Control ECO™/ECO™ Off/Work modes	Battery	12 V (30 amp/h)	
Power Steering	Dynamic Power Steering (DPS)	Magneto	650 W	
SUSPENSIONS		Instrumentation	Two lighter-type DC outlets, one in the console (20 A) and one in the under dash storage (20 A)	
Front Suspension	Arched double A-arm with sway bar/10 in. (25.4 cm) travel	Lighting	140 W lighting output from four 35 W reflectors	
Front Shocks	Twin tube gas-charged shocks		ensuring a wide visiblity, signature LED and LED tail lights	
Rear Suspension	Arched TTA with external sway bar/10 in. (25.4 cm) travel	Winch	Relocated 4,500 lb (2,041 kg) winch with synthetic	
Rear Shocks	Twin tube gas-charged shocks		rope and roller fairlead	
TYRES & WHEELS		Seat	VERSA-PRO bolster bench seats for additional lateral support, passenger seats flipping up, adjustable driver seat, underside hooks, reinforced seat skin featuring X package trims and contoured bench to improve entrance/exit	
Front Tyres ITP Cryptid 30 x 9 x 14 in.				
Rear Tyres	ITP Cryptid 30 x 11 x 14 in.		of the cab	
Wheels	14 in. cast-aluminum	Steering Wheel	Adjustable tilt steering	
BRAKES		Protection	Heavy-duty front steel bumper, HMWPE full skid plate	
Front	Dual 220 mm disc brakes with hydraulic twin-piston		aluminum rock sliders, mudguards	
	calipers	Hitch Type	2 in. hitch receiver	
Door	Dual 220 mm disa brakas with budraulis single pieten	MARDANITY & CEDVICE		



WARRANTY & SERVICE

Factory Warranty

Service Intervals

Dual 220 mm disc brakes with hydraulic single-piston

calipers

Brake-holding mechanism



2 years/15,000 km warranty,

whichever comes first

200 hrs / 12 months / 3,000 km